


## Cuscinetti a rullini NA49-32-U-IKO - NA49-32-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/na49-32-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
32	—	NA 49/32U <sup>1)</sup>	—	—	167	32	52	20	21
$r_s$ min	Standard mounting dimensions mm		Basic static load rating C <sub>0</sub>	Basic dynamic load rating C <sub>10</sub>	Allowable rotational speed <sup>2)</sup> rpm	Assembled inner ring			
0.6	40	36 39 48	29 400	44 200	5 000	LRTZ 324021			

Notes: 1) Minimum allowable value of shaft diameter r.  
2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
3) Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952381428
Diametro interno	32 mm
Diametro interno	1.26" inch
Diametro esterno	52 mm
Diametro esterno	2.047" inch
Spessore	21 mm
Spessore	0.827" inch
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE