


Cuscinetti a rullini NA4910-U-IKO - NA4910-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/na4910-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
50	—	NA 4910U	—	—	295	50	72	22	23
r_s min	Standard mounting dimensions mm		Basic rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring			
0.6	Min. 58 Max. 54	Max. 57 Min. 68	N 41 300	N 71 100	3 500	LRTZ 505823			

Notes: (1) Minimum allowable value of diameter dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952381589
Diametro interno	50 mm
Diametro esterno	72 mm
Spessore	23 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE