


## Cuscinetti a rullini NA6918-U-IKO - NA6918-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/na6918-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
90	—	—	—	—	NA 6918U	2 480	90	125	63	64

$r_s$ min (1)	$F_w$	Standard mounting dimensions mm		Basic static load rating $C_0$ N	Basic dynamic load rating $C$ N	Allowable rotational speed(2) rpm	Assembled inner ring LRTZ 9010564	
		Min.	Max.					
1.1	105	96.5	103	118.5	172 000	471 000	1 800	LRTZ 9010564

Notes(1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952381916
Diametro interno	90 mm
Diametro esterno	125 mm
Spessore	64 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE