

## Cuscinetti a rullini NA4919-U-IKO - NA4919-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/na4919-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
95	—	NA 4919U	—	—	1 420	95	130	35	36

r <sub>s</sub> min <sup>(1)</sup>	F <sub>w</sub>	Standard mounting dimensions mm		Basic static load rating C <sub>0</sub> N	Basic dynamic load rating C <sub>10</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring LRTZ 9511036
		d <sub>s</sub> Min.	d <sub>s</sub> Max.				
1.1	110	101.5	108	123.5	109 000	250 000	1 700

Notes: (1) Minimum allowable value of shaft dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952381947
Diametro interno	95 mm
Diametro esterno	130 mm
Spessore	36 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE