


Cuscinetti a rullini NA4928-UU-IKO - NA4928-UU-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/na4928-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|------------------|-----------------------|---------------|----------------|---------------|---------------------|---------------------------|-----|----|----|
| | With two seals | With one seal | With two seals | With one seal | | d | D | C | B |
| 140 | NA 4928UU | — | — | — | 4 340 | 140 | 190 | 50 | 51 |

| r _s min (¹⁾) | Standard mounting dimensions mm | | | | Basic static load rating C ₀ N | Allowable rotational speed (²⁾) rpm | Assembled inner ring LRTZ 14016051 |
|---|------------------------------------|---------------------|---------------------|---------------------|---|--|---------------------------------------|
| | F _w | d _s Min. | d _s Max. | D _s Max. | | | |
| 1.5 | 160 | 148 | 158 | 182 | 214 000 | 549 000 | 1 200 |

Notes: (¹) Minimum allowable value of shaft diameter r.
(²) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952382050 |
| Diametro interno | 140 mm |
| Diametro esterno | 190 mm |
| Spessore | 51 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE