


Cuscinetti a rullini BRI102216-U-IKO - BRI102216-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/bri102216-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
15.875 ($\frac{3}{4}$)		BRI 102216 U	113.5	15.875 ($\frac{3}{4}$)	34.925 (1 $\frac{3}{4}$)	25.400 (1)	25.650
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRBZ 101416 B
	Min.	Max.	Max.				
22.225 ($\frac{7}{8}$)	21	21.2	29.7	0.6	21 600	26 900	9 000

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952382517
Diametro interno	15.875 mm
Diametro esterno	34.925 mm
Spessore	25.4 mm
Peso	150 g
Imballaggio	-
Standard	Nessuno standard

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE