


Cuscinetti a rullini BRI142620-U-IKO - BRI142620-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/bri142620-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | |
|-----------------------------|-----------------------------------|---------------------|-------------------------------------|--|--|---------------------------|--------|---------------|
| | With two seals | With one seal | | d | D | C | B | |
| 22.225 ($\frac{7}{8}$) | | BRI 142620 U | 177 | 22.225 ($\frac{7}{8}$) | 41.275 ($1\frac{3}{4}$) | 31.750 ($1\frac{1}{4}$) | 32.000 | |
| F_w | Standard mounting dimensions (mm) | | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | | |
| | Min. | Max. | | | | | Min. | Max. |
| 28.575 ($1\frac{1}{4}$) | 27 | 27.5 | 36.0 | 0.6 | 34 900 | 49 900 | 7 000 | LRBZ 141820 B |

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952382555 |
| Diametro interno | 22.225 mm |
| Diametro esterno | 41.275 mm |
| Spessore | 31.75 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE