


Cuscinetti a rullini BRI183020-U-IKO - BRI183020-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/bri183020-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
28.575 (1 $\frac{1}{4}$)		BRI 183020 U	211	28.575 (1 $\frac{1}{4}$)	47.625 (1 $\frac{3}{4}$)	31.750 (1 $\frac{1}{4}$)	32.000	
F_w	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring		
	Min.	Max.				Min.	Max.	
	33.5	33.9	42.4	0.6	38 500	60 000	5 500	LRBZ 182220 B

Notes:
(1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark:
1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952382593
Diametro interno	28.575 mm
Diametro esterno	47.625 mm
Spessore	31.75 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE