


## Cuscinetti a rullini BRI223520-U-IKO - BRI223520-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/bri223520-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		$d$	$D$	$C$	$B$	
<b>34.925</b> (1 $\frac{3}{8}$ )		<b>BRI 223520 U</b>	275	34.925 (1 $\frac{3}{8}$ )	55.562 (2 $\frac{1}{4}$ )	31.750 (1 $\frac{1}{4}$ )	32.000	
$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring LRBZ 222620 B	
	Min.	Max.	$r$ as max.					
	40.2	40.2	48.3	44 800	70 900	4 500		

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952382630
Diametro interno	34.925 mm
Diametro esterno	55.562 mm
Spessore	31.75 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE