


## Cuscinetti a rullini BRI264120-U-IKO - BRI264120-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/bri264120-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		$d$	$D$	$C$	$B$
<b>41.275</b> (1 5/8)		<b>BRI 264120 U</b>	386	41.275 (1 5/8)	65.088 (2 5/8)	31.750 (1 1/4)	32.000
$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring LRBZ 263220 B
	Min.	Max.	Max. as max. <sup>(1)</sup>				
50.800 (2 )	48	49	57.8	1	51 000	89 400	4 000

Notes: (1) Minimum allowable value of chamfer dimension  $r$   
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952382685
Diametro interno	41.275 mm
Diametro esterno	65.088 mm
Spessore	31.75 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE