


## Cuscinetti a rullini BRI325228-U-IKO - BRI325228-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/bri325228-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
50.800 (2)		<b>BRI 325228 U</b>	889	50.800 (2)	82.550 (3 $\frac{1}{2}$ )	44.450 (1 $\frac{3}{4}$ )	44.700	
$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring		
	Min.	Max.					$d_s$	$D_s$ Max.
63.500 (2 $\frac{1}{2}$ )	58	61	74.3	1.5	94 600	174 000	3 000	<b>LRBZ 324028 B</b>

Notes: (\*) Minimum allowable value of chamfer dimension r  
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952382722
Diametro interno	50.8 mm
Diametro esterno	82.55 mm
Spessore	44.45 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE