


Cuscinetti a rullini BRI325228-UU-IKO - BRI325228-UU-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/bri325228-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
50.800 (2)	BRI 325228 UU		889	50.800 (2)	82.550 (3 $\frac{1}{2}$)	44.450 (1 $\frac{3}{4}$)	44.700	
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ^(*) rpm	Assembled inner ring	
	Min.	Max.	Max. as max. ^(*)					
63.500 (2 $\frac{1}{2}$)	58	61	74.3	1.5	94 600	174 000	3 000	LRBZ 324028 B

Notes: (*) Minimum allowable value of chamfer dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952382739
Diametro interno	50.8 mm
Diametro esterno	82.55 mm
Spessore	44.45 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE