


Cuscinetti a rullini BRI446828-UU-IKO - BRI446828-UU-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/bri446828-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
69.850 (2 3/4)	BRI 446828 UU		1 421	69.850 (2 3/4)	107.950 (4 1/4)	44.450 (1 3/4)	44.700	
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ^(*) rpm	Assembled inner ring LRBZ 445228 B	
	Min.	Max.	Max.					
82 550 (3 1/4)	77	79	99.7	1.5	109 000	227 000	2 500	

Notes: (*) Minimum allowable value of diameter dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952382784
Diametro interno	69.85 mm
Diametro esterno	107.95 mm
Spessore	44.45 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE