


Cuscinetti a rullini BRI527632-UU-IKO - BRI527632-UU-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/bri527632-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
82.550 (3 1/4)	BRI 527632 UU		1 851	82.550 (3 1/4)	120.650 (4 3/4)	50.800 (2)	51.050	
F_w	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring		
	Min.	Max.						
95.250 (3 3/4)	91	93	148 000	287 000	2 000	LRBZ 526032 B		

Notes: (*) Minimum allowable value of diameter dimension r.
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952382821
Diametro interno	82.55 mm
Diametro interno	3 1/4" inch
Diametro esterno	120.65 mm
Diametro esterno	4 3/4" inch
Spessore	50.8 mm
Spessore	2" inch
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE