


Cuscinetti a rullini BRI527632-U-IKO - BRI527632-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/bri527632-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | |
|----------------------------|-----------------------------------|---------------------|---------------------------------------|--|--|----------------------|--------|---------------|
| | With two seals | With one seal | | d | D | C | B | |
| 82.550 (3 1/4) | | BRI 527632 U | 1 851 | 82.550 (3 1/4) | 120.650 (4 3/4) | 50.800 (2) | 51.050 | |
| F_w | Standard mounting dimensions (mm) | | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | | |
| | Min. | Max. | | | | Min. | Max. | |
| 95.250 (3 3/4) | 91 | 93 | 111.4 | 1.5 | 148 000 | 287 000 | 2 000 | LRBZ 526032 B |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952382838 |
| Diametro interno | 82.55 mm |
| Diametro esterno | 120.65 mm |
| Spessore | 50.8 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE