


Cuscinetti a rullini GBR122016-U-IKO - GBR122016-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/gbr122016-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | |
|---------------------------------|----------------------------------|---------------------------------|----------------------------------|---|----------------|------------|
| | With two seals | With 6/8e seal | | F_w | D | C |
| 19.050 (3/4) | GBR 122016 UU | | 79 | 19.050 7/8 | 31.750 1 1/4 | 25.400 1 |
| Standard mounting dimensions mm | | Ball dynamic load rating C | Ball static load rating C_0 | Allowable rotational speed ^(*) | | |
| D_s Max. | r as max (^(†)) | N | N | rpm | | |
| 27 | 0.6 | 26 400 | 34 500 | 4 000 | | |

Notes: (*) Minimum allowable value of diameter dimension r
(†) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952382876 |
| Diametro interno | 19.05 mm |
| Diametro esterno | 31.75 mm |
| Spessore | 25.4 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE