


## Cuscinetti a rullini GBR162416-U-IKO - GBR162416-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/gbr162416-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With 6/8e seal		$F_w$	$D$	$C$
25.400 (1)	GBR 162416 UU		99	25.400 (1)	38.100 (1) $\frac{1}{2}$	25.400 (1)
Standard mounting dimensions mm		Ball dynamic load rating $C$	Ball static load rating $C_0$	Allowable rotational speed <sup>(2)</sup>		
$D_s$ Max.	$r$ as max ( <sup>(1)</sup> )	N	N	rpm		
33.3	0.6	31 000	46 100	3 000		

Notes: (1) Minimum allowable value of diameter dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952382913
Diametro interno	25.4 mm
Diametro esterno	38.1 mm
Spessore	25.4 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE