


Cuscinetti a rullini GBR303920-U-IKO - GBR303920-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/gbr303920-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | |
|---------------------------------|-----------------------|---------------------------------|----------------------------------|---|----------------|----------------|
| | With two seals | With one seal | | F_w | D | C |
| 47.625 (1 7/8) | GBR 303920 UU | | 240 | 47.625 (1 7/8) | 61.912 (2 3/8) | 31.750 (1 1/4) |
| Standard mounting dimensions mm | | Seal dynamic load rating C | Ball static load rating C_0 | Allowable rotational speed ^(*) | | |
| D_A | r as max | N | N | rpm | | |
| 56.2 | 1 | 61 100 | 121 000 | 1 700 | | |

Notes: (*) Minimum allowable value of diameter dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952383057 |
| Diametro interno | 47.625 mm |
| Diametro esterno | 61.912 mm |
| Spessore | 31.75 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE