


Cuscinetti a rullini TRU10515350-IKO - TRU10515350-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/tru10515350-iko>

IKO

ROLLER BEARINGS

Caged Roller Bearings
Full Complement Roller Bearings



NAU49 TRU

| Shaft dia. mm | Identification number | | Mass (Ref.) g | Boundary dimensions mm | | | | | |
|-----------------------------|-----------------------------------------|-------------------------------------------|---------------|------------------------|-----|----|-------------------------------------|-----|----------------|
| | Full complement type | Caged type | | d | D | C | r ⁽¹⁾ F _s min | J | E _w |
| 105 | — | — TRU 10515350 | 2 890 | 105 | 153 | 50 | 1.5 | 120 | 138 |
| Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽²⁾ | | | | | | | |
| N | N | rpm | | | | | | | |
| 159 000 | 286 000 | 3 500 | | | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952385716 |
| Diametro interno | 105 mm |
| Diametro esterno | 153 mm |
| Spessore | 50 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE