




## Cuscinetti a rullini TRU405930-UU-IKO - TRU405930-UU-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/tru405930-uu-iko>

**IKO**  
**ROLLER BEARINGS**  
Caged Roller Bearings   
Full Complement Roller Bearings 



Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r <sub>min</sub> <sup>(1)</sup>	J
40	---	TRU 405930UU	265	40	59	30	0.6	45
<i>E<sub>w</sub></i>	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>					
52.5	N 34 700	N 62 500	r/min 4,000					

Notes: <sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAU and NAG series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952386034
Diametro interno	40 mm
Diametro interno	1.575" inch
Diametro esterno	59 mm
Diametro esterno	2.323" inch
Spessore	30 mm
Spessore	1.181" inch
Peso	270 g
Imballaggio	-
Standard	Nessuno standard

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE