


Cuscinetti a rullini
TRU7510845-UU-IKO - TRU7510845-UU-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/tru7510845-uu-iko>


ROLLER BEARINGS
Caged Roller Bearings 
Full Complement Roller Bearings 


NAU49-UU
TRU-UU

Shaft dia. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r _s min	J
75	---	---	TRU 7510845UU	1 240	75	108	45	1	85.5
	Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed r/min						
98.5	103 000	190 000	2 000						

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: The NAU and TRU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952386324
Diametro interno	75 mm
Diametro esterno	108 mm
Spessore	45 mm
Imballaggio	1

contatto@123cuscinetti.ch
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE