



Cuscinetti a rullini NAS5011-UU-NR-IKO - NAS5011-UU-NR-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/nas5011-uu-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves

NAS50-UUNR

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
55	NAS 5011UUNR		1.15	55	90	94.8	46	45	34	5.5
<i>f</i>	<i>c</i>	<i>r</i> mm ⁽¹⁾	<i>J</i>	Basic dynamic load rating C ₀ N	Static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm				
2.5	2	0.6	68	118 000	193 000	1 800				

Notes⁽¹⁾ Minimum allowable value of chamfer dimension *r*
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAS and NAU series with a bore diameter, *d*, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952386805
Diametro interno	55 mm
Diametro esterno	90 mm
Spessore	46 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE