


Cuscinetti a rullini
NAS5014-UU-NR-IKO - NAS5014-UU-NR-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/nas5014-uu-nr-iko>



ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
70	NAS 5014UU	NR	1.90	70	110	114.5	54	53	42	5.5

f	c	r _s (1)	J	Basic dynamic load rating C _r N	Static load rating C ₀ N	Allowable rotational speed (2) rpm
2.5	2	0.6	84	171 000	284 000	1 400

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAS and NAG series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952386850
Diametro interno	70 mm
Diametro esterno	110 mm
Spessore	54 mm
Peso	1955 g
Imballaggio	1

contatto@123cuscinetti.ch
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE