


Cuscinetti a rullini NAS5018-ZZ-NR-IKO - NAS5018-ZZ-NR-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/nas5018-zz-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
90		NAS 5018ZZNR	3.70	90	140	145.4	67	66	54	6

f	c	r _s mm ⁽¹⁾	J	Basic dynamic load rating C _r N	Static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm
2.5	2.5	0.6	110	305 000	540 000	1 100

Notes^(*)
⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952386942
Diametro interno	90 mm
Diametro esterno	140 mm
Spessore	67 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE