



## Cuscinetti a rullini NAS5019-ZZ-NR-IKO - NAS5019-ZZ-NR-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/nas5019-zz-nr-iko>

IKO  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves

NAS50-ZZNR

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm							
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S	
95		NAS 5019ZZNR	3.90	95	145	150.4	67	66	54	6	
	f	c	r <sub>s</sub> mm <sup>(1)</sup>	J	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm				
	2.5	2.5	0.6	114	312 000	562 000	1 100				

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952386959
Diametro interno	95 mm
Diametro interno	3.74" inch
Diametro esterno	145 mm
Diametro esterno	5.709" inch
Spessore	67 mm
Spessore	2.638" inch
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE