



Cuscinetti a rullini NAS5022-ZZ-NR-IKO - NAS5022-ZZ-NR-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/nas5022-zz-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves

NAS50-ZZNR

| Shaft dia. mm | Identification number | | Mass (Ref.) kg | Boundary dimensions mm | | | | | | |
|---------------|-----------------------|----------------------------|----------------|-------------------------------|-----|-------------------------------------|----|---|----------------|---|
| | Sealed type | Shield type | | d | D | D ₂ | B | C | C ₁ | S |
| 110 | | NAS 5022ZZNR | 6.50 | 110 | 170 | 175.4 | 80 | 79 | 65 | 7 |
| <i>f</i> | <i>c</i> | <i>r</i> mm ⁽¹⁾ | <i>J</i> | Basic dynamic load rating C N | | Static load rating C ₀ N | | Allowable rotational speed ⁽²⁾ rpm | | |
| 2.5 | 3 | 1 | 130 | 364 000 | | 697 000 | | 900 | | |

Notes^(*) Minimum allowable value of chamfer dimension *r*
⁽¹⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAS and NAU series with a bore diameter, *d*, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952386997 |
| Diametro interno | 110 mm |
| Diametro interno | 4.331" inch |
| Diametro esterno | 170 mm |
| Diametro esterno | 6.693" inch |
| Spessore | 80 mm |
| Spessore | 3.15" inch |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE