


Cuscinetti a rullini NAS5024-UU-NR-IKO - NAS5024-UU-NR-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/nas5024-uu-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



| Shaft dia. mm | Identification number | | Mass (Ref.) kg | Boundary dimensions mm | | | | | | |
|---------------|-----------------------|----------------------------|----------------|-------------------------------|-------------------------------------|---|----|----|----------------|---|
| | Sealed type | Shield type | | d | D | D ₂ | B | C | C ₁ | S |
| 120 | NAS 5024UUNR | | 6.95 | 120 | 180 | 188.4 | 80 | 79 | 65 | 7 |
| <i>f</i> | <i>c</i> | <i>r</i> mm ⁽¹⁾ | <i>J</i> | Basic dynamic load rating C N | Static load rating C ₀ N | Allowable rotational speed ⁽²⁾ rpm | | | | |
| 3 | 3 | 1 | 139.5 | 400 000 | 750 000 | 850 | | | | |

Notes⁽¹⁾ Minimum allowable value of chamfer dimension *r*
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAS and NAU series with a bore diameter, *d*, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952387017 |
| Diametro interno | 120 mm |
| Diametro esterno | 180 mm |
| Spessore | 80 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE