



Cuscinetti a rullini NAS5030-ZZ-NR-IKO - NAS5030-ZZ-NR-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/nas5030-zz-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves

NAS50-ZZNR

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
150		NAS 5030ZZNR	13.5	150	225	233.4	100	99	81	9
<i>f</i>	<i>c</i>	<i>r_s</i> mm ⁽¹⁾	<i>J</i>	Basic dynamic load rating C ₀ N	Static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm				
3	3.5	1	176.5	629 000	1 210 000	650				

Notes: (1) Minimum allowable value of chamfer dimension *r*.
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAG and NAU series with a bore diameter, *d*, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952387079
Diametro interno	150 mm
Diametro interno	5.906" inch
Diametro esterno	255 mm
Diametro esterno	10.039" inch
Spessore	100 mm
Spessore	3.937" inch
Peso	13500 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE