


Cuscinetti a rullini NAX6040Z-IKO - NAX6040Z-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/nax6040z-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring



| Identification number | | | | | | | | | | | | | | |
|---------------------------|---------------------|-------|-----------------|-----|---------------------|-----------|-----------------|--------------------------|-----------------------------------|---|--------|---------|--------|-------|
| Shaft dia. mm | Mass (Ref.) g | | With dust cover | | Mass (Ref.) g | | With dust cover | | Mass (Ref.) g | | | | | |
| | NAX 6040Z | | 454 | | --- | | --- | | | | | | | |
| Boundary dimensions mm | | | | | | | | | | | | | | |
| F_w | D | D_1 | D_2 | L | H | r_1 min | d_1 | Basic load rating C | Basic static load rating C_0 | Allowable rotational speed ⁽²⁾ | | | | |
| 60 | 72 | 85 | 86.5 | 40 | 17 | 12 | 1 | 60 | 75 | 47 500 | 41 400 | 103 000 | 89 700 | 4 000 |

Notes:
(1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952390376 |
| Diametro interno | 60 mm |
| Diametro esterno | 72 mm |
| Spessore | 40 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE