


Cuscinetti a rullini NAX7040Z-IKO - NAX7040Z-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/nax7040z-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring



| Identification number | | | | | | | | | | |
|---------------------------|------------------|-----------|-----------------|-----|------------------|------------|-----------------|--------------------------|-----------------------------------|--|
| Shaft dia. mm | Mass (Ref.) g | | With dust cover | | Mass (Ref.) g | | With dust cover | | Mass (Ref.) g | |
| | 70 | NAX 7040Z | | 606 | | — | | — | | — |
| Boundary dimensions mm | | | | | | | | | | |
| F_w | D | D_1 | D_2 | L | H | r_1 min. | d_f | Basic load rating C | Basic static load rating C_0 | Allowable rotational speed ⁽²⁾ rpm |
| 70 | 85 | 95 | 96.5 | 40 | 18 | 1 | 70 | 55 500 | 43 100 | 120 000 / 101 000 |

Notes:
(1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952390550 |
| Diametro interno | 70 mm |
| Diametro interno | 2.756" inch |
| Diametro esterno | 85 mm |
| Diametro esterno | 3.346" inch |
| Spessore | 40 mm |
| Spessore | 1.575" inch |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE