

## Cuscinetti a rullini NAXI1223-IKO - NAXI1223-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/naxi1223-iko>

**IKO**

**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing With Inner Ring  
Needle Roller Bearings with Thrust Roller Bearing With Inner Ring

Shaft dia. mm	Identification number						d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
12	<b>NAXI 1223</b>	55.5	—	—	—	—	12	24	28

  

Boundary dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
D <sub>2</sub>	L	B	H		Radial	Axial			
25	23	16	9	8 230	10 000	9 190	11 100	9 500	LRT 71016

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
 Remarks: 1. The outer ring has an oil groove and an oil hole.  
 2. Grease is not prepacked. Perform proper lubrication.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952390680
Diametro interno	12 mm
Diametro esterno	24 mm
Spessore	23 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE