


## Cuscinetti a rullini NBXI3030-IKO - NBXI3030-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/nbxi3030-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**



Shaft dia. mm	Identification number						d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
30	---	---	<b>NBXI 3030</b>	<b>225</b>	---	---	30	47	52

Boundary dimensions mm				Bore chamfer mm	Bore chamfer mm	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring LRT 303520					
D <sub>2</sub>	L	B	H				Radial	Radial			Axial	Axial			
53	30	20	12	9	0.6	0.3	35	50	34	26 900	29 100	46 200	91 100	7 000	

Notes:  
(1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remark 1: The outer ring has an oil groove and an oil hole.  
2: Grease is not prepacked. Perform proper lubrication.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952390901
Diametro interno	30 mm
Diametro esterno	47 mm
Spessore	30 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE