


## Cuscinetti a rullini NBXI3532Z-IKO - NBXI3532Z-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/nbxi3532z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**



Shaft dia. mm	Identification number						d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
35	---	---	---	<b>NBXI 3532Z</b>		294	35	52	60

Boundary dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring				
D <sub>2</sub>	L	B	H		Radial	Axial						
61	32	20	13	40	57	39	29 400	41 700	54 100	133 000	6 000	LRT 354020

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.  
 Remarks: Z. The outer ring has an oil groove and an oil hole.  
 Z. Grease is not prepacked. Perform proper lubrication.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952390956
Diametro interno	35 mm
Diametro interno	1.378" inch
Diametro esterno	52 mm
Diametro esterno	2.047" inch
Spessore	32 mm
Spessore	1.26" inch
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE