


## Snodi sferici GE SB6510555-IKO - SB6510555-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/sb6510555-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree $\alpha$
	SB	6510555		d	D	B	C	d <sub>k</sub>	r <sub>1</sub> <sup>(1)</sup> mm	
65	SB	6510555	2.05	65	105	55	47	94	0.6	5
Mounting dimensions mm				Dynamic load capacity C <sub>d</sub> N	Static load capacity C <sub>s</sub> N					
d <sub>s</sub>	D <sub>s</sub>									
Min.	Max. <sup>(2)</sup>	Min.								
69.5	76	100.5	87	433 000	2 600 000					

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>.  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>s</sub>.  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952391397
Diametro interno	65 mm
Diametro esterno	105 mm
Spessore	55 mm
Tipo	GE
Peso	2050 g
Lubrificazione	senza
Imballaggio	-
Standard	Nessuno standard

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE