


Snodi sferici GE
GE100ES-2RS-IKO - GE100ES-2RS-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/ge100es-2rs-iko>



SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



GE-ES-2RS

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degrees			
	Without seals	With seals		A	D	B	C	d _s	r ₁ (1)	r ₂ (1)	α	α _l	
100		GE 100ES-2RS	4.43	100	150	70	55	130	1	1	7	5	
Mounting dimensions mm		Dynamic load capacity C _d N	Static load capacity C _s N										
d _s	D _s			d _s	D _s	d _s	D _s	d _s	D _s	d _s	D _s	d _s	D _s
Min.	Max.(2)	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
105.5	109.5	144.5	127										

Notes(1)
(1) Minimum allowable value of chamfer dimensions r₁ and r₂
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.

Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952391960
Diametro interno	100 mm
Diametro esterno	150 mm
Spessore	70 mm
Tipo	GE
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE