


Snodi sferici GE
GE180ES-IKO - GE180ES-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/ge180es-iko>



SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		A	D	B	C	d _s	r ₁ (1)	r ₂ (1)	α	α _l
180	GE 180ES		18.9	180	260	105	80	225	1.1	1.1	6	5
Mounting dimensions mm				Dynamic load capacity C _d		Static load capacity C _s						
d _s		D _s		N		N						
Min.	Max.(2)	Max.	Min.									
187	199	253	221	1 770 000		10 600 000						

Notes(1)
(1) Minimum allowable value of chamfer dimensions r₁ and r₂
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.

Remark(1)
1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952392042
Diametro interno	180 mm
Diametro esterno	260 mm
Spessore	105 mm
Tipo	GE
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE