


Snodi sferici GE GE200ES-2RS-IKO - GE200ES-2RS-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/ge200es-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree			
	Without seals	With seals		d	D	B	C	d _s	r ₁ ⁽¹⁾ min	r ₂ ⁽¹⁾ min	α	α ₁	
200		GE 200ES-2RS	26,1	200	290	130	100	250	1,1	1,1	7	6	
Mounting dimensions mm		Dynamic load capacity C _d		Static load capacity C _s									
d _s		D _s		N		N							
Min.	Max. ⁽²⁾	Min.	Max.	Min.	Max.	Min.	Max.						
207	213,5	283	244	2 450 000	14 700 000								

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952392066
Diametro interno	200 mm
Diametro esterno	290 mm
Spessore	130 mm
Tipo	GE
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE