

## Snodi sferici GE GE300ES-IKO - GE300ES-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/ge300es-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		$d$	$D$	$B$	$C$	$d_s$	$r_1$ (1)	$r_2$ (1)	$\alpha$	$\alpha_1$
<b>300</b>	<b>GE 300ES</b>		<b>76.0</b>	<b>300</b>	<b>430</b>	<b>165</b>	<b>120</b>	<b>375</b>	<b>1.1</b>	<b>1.1</b>	<b>7</b>	<b>6</b>
Mounting dimensions mm		Dynamic load capacity $C_d$		Static load capacity $C_s$								
$d_s$		$D_s$		N		N						
Min.	Max.(2)	Max.	Min.	Min.	Max.	Min.	Max.					
307	336.5	423	371	4 410 000	26 500 000							

Notes (1) Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952392165
Diametro interno	300 mm
Diametro esterno	430 mm
Spessore	165 mm
Tipo	GE
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE