

Snodi sferici GE GE180GS-IKO - GE180GS-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/ge180gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d _s	r ₁ ⁽¹⁾ r _{1s} min	r ₂ ⁽¹⁾ r _{2s} min	α	α ₁
180	GE 180GS		34.7	180	290	155	100	250	1.1	1.1	14	13

Mounting dimensions mm				Dynamic load capacity C _d N	Static load capacity C _s N
d _s		D _s			
Min.	Max. ⁽²⁾	Max.	Min.		
187	196	283	244	2 450 000	14 700 000

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952392592
Diametro interno	180 mm
Diametro esterno	290 mm
Spessore	155 mm
Tipo	GE
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE