


Snodi sferici GE GE240GS-2RS-IKO - GE240GS-2RS-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/ge240gs-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



| Shaft dia. mm | Identification number | | Mass (ref.) kg | Boundary dimensions mm | | | | | | Permissible tilting angle degree | | | |
|---------------------------|-----------------------|--|---------------------------------------|---------------------------|-------------------|------------|------------|------------|----------------------|--|-----------|------------|--|
| | Without seals | With seals | | d | D | B | C | d_s | r_1 ⁽¹⁾ | r_2 ⁽¹⁾ | α | α_1 | |
| 240 | | GE 240GS-2RS | 66,1 | 240 | 370 | 190 | 110 | 325 | 1,1 | 1,1 | 15 | 14 | |
| Mounting dimensions mm | | Dynamic load capacity C_d N | Static load capacity C_s N | d_s | | D_s | | | | | | | |
| Min. | Max. ⁽²⁾ | | | Max. | Min. | Max. | Min. | Max. | | | | | |
| 247 | 263,5 | 363 | 320 | 3 510 000 | 21 000 000 | | | | | | | | |

Notes ⁽¹⁾ Minimum allowable value of chamfer dimensions r_1 and r_2 .
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952392653 |
| Diametro interno | 240 mm |
| Diametro esterno | 370 mm |
| Spessore | 190 mm |
| Tipo | GE |
| Lubrificazione | senza |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE