


## Snodi sferici GE GE260GS-IKO - GE260GS-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/ge260gs-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		$d$	$D$	$B$	$C$	$d_s$	$r_1$ <sup>(1)</sup>	$r_2$ <sup>(1)</sup>	$\alpha$	$\alpha_1$
<b>260</b>	<b>GE 260GS</b>		<b>81,8</b>	<b>260</b>	<b>400</b>	<b>205</b>	<b>120</b>	<b>350</b>	<b>1,1</b>	<b>1,1</b>	<b>15</b>	<b>14</b>
Mounting dimensions mm			Dynamic load capacity $C_d$ N	Static load capacity $C_s$ N								
$d_s$	$D_s$				Min.	Max. <sup>(2)</sup>	Min.	Max.	Min.	Max.	Min.	Max.
267	283,5	393	345	4 120 000	24 700 000							

Notes <sup>(1)</sup> Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952392677
Diametro interno	260 mm
Diametro esterno	400 mm
Spessore	205 mm
Tipo	GE
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE