



Snodi sferici GE SBB56-2RS-IKO - SBB56-2RS-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-sno-do/ge/sbb56-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings Inch Series

Permissible tilting angle
SBB--2RS

Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
88.900 (3 1/2)		SBB 56-2RS	4.83	88.900 (3 1/2)	139.700 (5 1/2)	77.77 (3.062)	66.68 (2.625)
Radial internal clearance mm	Mounting dimensions mm		Dynamic load capacity C _d N	Static load capacity C _s N			
	d _k Min./Max.	d ₁ r ₁ max. r ₂ max.		C _d N	C _s N	C _s N	
128(5.039)	0.13 / 0.23	101.6 0.6 0.8	837 000	5 020 000			

Notes: (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_k.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952392974
Diametro interno	88.9 mm
Diametro esterno	139.7 mm
Spessore	77.77 mm
Tipo	GE
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE