



Snodi sferici GE SBB76-IKO - SBB76-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/sbb76-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings Inch Series

Permissible tilting angle SBB

Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
120.650 (4 7/8)	SBB 76		11.6	120.650 (4 7/8)	187.325 (7 1/2)	105.56 (4.156)	90.47 (3.562)
d _k	Radial internal clearance mm Min./Max.	Mounting dimensions mm d ₁ r ₁ max. r ₂ max.	Dynamic load capacity C _d N	Static load capacity C _s N			
173 (6.811)	0.13 / 0.23	136.8 0.8 1.1	1 530 000	9 210 000			

Notes: (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_k.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952393063
Diametro interno	120.65 mm
Diametro esterno	187.325 mm
Spessore	105.56 mm
Tipo	GE
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE