


Snodi sferici GE SBB96-IKO - SBB96-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/sbb96-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
152.400 (6)	SBB 96		17.6	152.400 (6)	222.250 (8 7/8)	120.65(4.750)	104.78(4.125)
Radial internal clearance mm Min./Max.	Mounting dimensions mm		Dynamic load capacity C _d N	Static load capacity C _s N			
	d _k	d ₁ r ₁ max. r ₂ max.		C _d	C _s	C _s	
207(8.150)	0.13 / 0.23		167.5	0.8	1.1	2 130 000	12 800 000

Notes: (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_k.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952393100
Diametro interno	152.4 mm
Diametro esterno	222.25 mm
Spessore	120.65 mm
Tipo	GE
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE