

Rotelle con perno CFES6-UUR-IKO - CFES6-UUR-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cfes6-uur-iko>

IKO

CAM FOLLOWERS

Solid Eccentric Stud Type Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d ₁
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
6			CFES 6	UUR	18.5	16	11	6

Boundary dimensions mm										
G	G ₁	B	B ₁	B ₂	B ₃	C ₁	B ₁	β ₂	ε _{max} (°)	E
M 6×1	8	12.2	28.2	16	—	0.6	*4	—	0.3	0.25

Mounting dimension f _{min}	Maximum tightening torque	Back dynamic load rating C	Back static load rating C ₀	Maximum allowable static load
mm	N·m	N	N	N
11	2.7	3 660	3 650	1 980

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060459060
Diametro interno	6 mm
Diametro esterno	16 mm
Spessore	11 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE