


Rotelle con perno CFE12-UU-IKO - CFE12-UU-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cfe12-uu-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)					
	Shield type		Sealed type		\emptyset	D	C	d_2		
16	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 12	UU	105	30	14	16

Boundary dimensions mm										Eccentricity e	Mounting dimension f Min. mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C_0 N	Maximum allowable static load N
G	B_3	B max	B_1 max	B_2	C_1	G_1	r_{max}	r_{min}	r						
M12X1.5	11.5	15.2	40.2	25	0.6	6	13.5	0.6	0.8	21	21.9	7 910	9 790	9 790	

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060459916
Diametro interno	16 mm
Diametro interno	0.63" inch
Diametro esterno	30 mm
Diametro esterno	1.181" inch
Spessore	14 mm
Spessore	0.551" inch
Peso	105 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE