


Rotelle con perno CFE12-1-UUR-IKO - CFE12-1-UUR-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cfe12-1-uur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)									
	Shield type		Sealed type		\emptyset	D	C	d_2						
16	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	115	32	14	16						
CFE 12-1 UUR														
Boundary dimensions mm														
G	B ₃	B _{max}	B _{1 max}	B ₂	C ₁	g ₁	G ₁	(1) $\frac{f}{g}$	Mounting dimension f Min. mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
M 8×1.25	9.5	12.2	32.2	20	0.6	*4	10.5	0.3	0.4	13	6.5	4 250	4 740	4 620

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060459947
Diametro interno	16 mm
Diametro interno	0.63" inch
Diametro esterno	32 mm
Diametro esterno	1.26" inch
Spessore	14 mm
Spessore	0.551" inch
Peso	115 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE