


Rotelle con perno CFE6-VUUR-IKO - CFE6-VUUR-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cfe6-vuur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot



Outside diameter of eccentric outer ring mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
9	CFE 6 VUUR				21	16	11	9

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum operating torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
G	B ₃	B max	B ₂ max	B ₂	C ₁	β ₁	G ₁	r ₁ min	Eccentricity E					
M 6 × 1	7.5	12.2	28.2	16	0.6	*4	8.5	0.3	0.4	11	2.7	6 980	8 500	1 950

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060460875
Diametro interno	9 mm
Diametro esterno	16 mm
Spessore	11 mm
Peso	21 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE