

Rotelle con perno CF-FU1-24-IKO - CF-FU1-24-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cf-fu1-24-iko>

IKO

CAM FOLLOWERS

Centralized Lubrication Type Cam Followers With Cage/With Screwdriver Slot



| Stud dia. mm | Identification number | | Mass (Ref.) g | Boundary dimensions mm | | | | |
|-----------------|----------------------------|--------------------------------|---------------------|------------------------|----|----------------|-----------|----------------|
| | With crowned outer ring | With cylindrical outer ring | | D | C | d ₁ | G | G ₁ |
| 24 | | CF-FU1-24 | 815 | 62 | 29 | 24 | M24 x 1.5 | 25 |

| B _{max} | B _{1max} | B ₂ | B ₃ | C ₁ | g ₂ | M ₁ | M ₂ | f _g min ⁽¹⁾ | Mounting dimension f _g Min. mm | Maximum tightening torque N-m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N |
|------------------|-------------------|----------------|----------------|----------------|----------------|----------------|----------------|-----------------------------------|---|--|--|--|--|
| 30.6 | 80.1 | 49.5 | 11 | 0.8 | 4 | PT 1/8 | PT 1/8 | 1 | 40 | 215 | 30 500 | 52 600 | 52 000 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3616060461711 |
| Diametro interno | 24 mm |
| Diametro esterno | 62 mm |
| Spessore | 29 mm |
| Peso | 815 g |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE