


Rotelle con perno CR24-BUUR-IKO - CR24-BUUR-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cr24-buur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Identification number				Mass (Ref.)	g	D	C	d ₁	G _{UNF}	G ₁
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
15.875 ($\frac{5}{8}$)	CR 24 BUUR				225	38.100 ($\frac{1 1}{2}$)	22.225 ($\frac{7}{8}$)	15.875 ($\frac{5}{8}$)	F ₁ -18	19.050 ($\frac{3}{4}$)	
Boundary dimensions mm/inch											
B	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm/ mm(inch)	Maximum spinning torque C	Basic dynamic load rating C	Basic static load rating C ₀
23.8 (0.93)	38.100 ($\frac{1 1}{2}$)	9.525 ($\frac{3}{8}$)	0.794 ($\frac{1}{16}$)	4.702 ($\frac{3}{16}$)	3.969 ($\frac{5}{32}$)	7.938 ($\frac{5}{16}$)	1.588 ($\frac{1}{16}$)	25.196 ($\frac{1 1}{8}$)	55.7	19.600	24.300

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060462602
Diametro interno	15.875 mm
Diametro esterno	38.1 mm
Spessore	22.225 mm
Peso	225 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE